

4.1. Fat client configurations

There are typically 2 types of startup configurations: 1 for a scanner, and 1 for a touchscreen. Below you can find 1 example of each:

SCANNER:

```
"C:\Program Files (x86)\Produmex\Produmex Fat Client\Produmex.Sbo.Logex.Execute.FatClient.exe"
/f- /a:Produmex.Foundation.SlimScreen.WinGui.PocketSize /s+ /w:240 /h:320 /i:SCANNER1
/cs:SboConnectionString
```

TOUCH:

```
"C:\Program Files (x86)\Produmex\Produmex Fat Client\Produmex.Sbo.Logex.Execute.FatClient.exe"
/f- /a:Produmex.Foundation.SlimScreen.WinGui.TouchScreen /s+ /w:1024 /h:768 /i:TOUCH1
/cs:SboConnectionString
```

Explanation for all the parameters:

Parameter	Description
/f-	f- means no fullscreen, f+ means fullscreen
/a:Produmex.Foundation.SlimScreen.WinGui.PocketSize	PocketSize is for scanner fatclient, TouchScreen is for touch fatclient
/s+	s+ means form is sizable, s- means not sizable. Ignored if 'FullScreen' is set.
/w:240	Screen width (pixels) , scanner default = 240, touch default = 1024. Ignored if 'FullScreen' is set.
/h:320	Screen height (pixels) , scanner default = 320, touch default = 768. Ignored if 'FullScreen' is set.
/i:SCANNER1	SCANNER01 is the code of the client defined in the organizational structure
/cs:SboConnectionString	Connection string tag name defined in fatclient config file.
/k:+	Show a keyboard.
/kp:50	The percentage of keyboard height.
/sp:50	The percentage of screen width.
/dilng:EN	The language to use in the DI API connection (overrides the Produmex.DI_API.Language app setting). Use language codes from the OLANG table (ShortName column). Default: EN.

From:
<https://wiki.produmex.name/> - **Produmex**

Permanent link:
<https://wiki.produmex.name/doku.php?id=implementation:wms:fatclientconfig&rev=1530018536>

Last update: **2018/06/26 13:08**

