

## 5.1.5. Reports

### 5.1.5.1. Overview

The Reports tab offers an overview of the standard reports that have been defined in Produmex.

It includes a reference to the shared folder (*Report path, Coresuite report path*) where the reports are stored and makes it possible to set the report parameters:

- Format in which the report is created (for example Crystal Reports, CoreSuite)
- Name
- Page size
- Orientation
- Type
- Path from the entered report path

The screenshot shows the 'Organizational Structure - Produmex Logex AddOn' window. The 'Reports' tab is selected, displaying the following configuration:

Code: ProdumexWMS\_Demo  
Name: PMX WMS Demo

Report Path: C:\Produmex\Reports  
Coresuite Report Path:   
CR Connection Name:   
Q

Key	Name	Path
1	Goods Receipt label	DefaultGoodsReceiptLabel.rpt
2	Weigh Order	DefaultWeighOrder.rpt

Format: Crystal reports (2) [Add] [Update] [Delete]  
Name: Goods Receipt label  
Page Size: A5 (A5)  
Orientation: Portrait (1)  
Type: GoodsReceiptLabel (GR-LBL)  
Path: DefaultGoodsReceiptLabel.rpt

Buttons: Ok, Cancel, Export, Close

### 5.1.5.2. Configuration

Step 1. Select the format you wish to use from the *Format* drop-down menu:

- A) Crystal Reports: uses the reports you download with your Produmex installation file.
- B) Crystal Reports by SAP: uses the default reports that are stored within SAP.
- C) Coresuite: uses the reports available in Coresuite.

- D) Unknown: can be used for custom report types.

Step 2. The next step depends on the format you have selected in step 1:

- A) **Crystal Reports:** Provide the path of the reports in the *Report Path* field.
  - MSSQL:  
You can find the reports in your installation folder and you can add its path to the *Report path* field, for example: *C:\Install\Produmex\_WMS\_X\_X.x64\Reports\MSSQL*.
  - HANA:  
Consult with [HANA Report Setting Tool](#).
    - *CR Connection Name* field (optional): If you use a HANA environment, some connection information needs to be provided for Crystal Reports, for example DbServer. By default, the *CR Connection Name* field is not filled in and the DbServer is used that is available from the connection. If the DbServer is not the right information for your report, fill in the *CR Connection Name field* and the value is passed to Crystal reports.
- B) **Crystal Reports by SAP:** Check the ID of the report, then add the ID into the *Path* field. When the system starts printing, it gets the report with this ID from the database.
- C) **Coresuite:** When printing the system creates a file to a certain folder. The field *Coresuite report path* needs to be filled in with a folder where the file needs to be stored. The Coresuite add-on picks up the file and prints the report.

Step 3. Provide the necessary report parameters.

- Name
- Page size
- Orientation
- Type
- Path from the entered report path

Step 4. Click ADD and the list of the added reports is displayed in the grid.

From:  
<https://wiki.produmex.name/> - **Produmex**

Permanent link:  
<https://wiki.produmex.name/doku.php?id=implementation:wms:reports&rev=1572887743>

Last update: **2019/11/04 17:15**

