

2.3. Example solutions

2.3.1 Get data from LogisticUnits parameter

Use the Get() method to read the parameter:

LogisticUnits.Get()

Example:

```
protected override void Execute()
{
    // Parameters in scope
    Session session = GetScopeParameter("Session") as Session;
    ISboProviderService sboProviderService =
    GetScopeParameter("<WwfService>ISboService") as ISboProviderService;

    foreach(LogisticUnitGoodsReceipt LUGR in LogisticUnits.Get()) {
        s_log.Error("CHECK DATA IN LOG - SSCC: " + LUGR.SSCC);
        foreach (LogisticUnitItemGoodReceipt LIGR in LUGR.ItemsOnLogisticUnit) {
            s_log.Error("CHECK DATA IN LOG - ItemCode: " + LIGR.ItemCode);
            s_log.Error("CHECK DATA IN LOG - Quantity: " +
            LIGR.Quantity.ToString());
            foreach (PackagingTypeInfo P in LIGR.FullListOfPackagingTypes){
                s_log.Error("CHECK DATA IN LOG - Uom: " + P.PackagingTypeName);
                s_log.Error("CHECK DATA IN LOG - Quantity: " + P.Quantity.ToString());
            }
        }
    }
}
```

From:

<https://wiki.produmex.name/> - **Produmex**

Permanent link:

https://wiki.produmex.name/doku.php?id=implementation:wms:wms_scripting_site:example_solutions

Last update: **2024/11/18 09:47**

