2.3. Example solutions

2.3.1 Get data from LogisticUnits parameter

Use the Get() method to read the parameter:
LogisticUnits.Get()

Example:

```
protected override void Execute()
{
// Parameters in scope
Session session = GetScopeParameter("Session") as Session;
ISboProviderService sboProviderService =
GetScopeParameter("<WwfService>ISboService") as ISboProviderService;

foreach(LogisticUnitGoodsReceipt LUGR in LogisticUnits.Get()) {
s_log.Error("CHECK DATA IN LOG - SSCC: " + LUGR.SSCC);
foreach (LogisticUnitItemGoodReceipt LIGR in LUGR.ItemsOnLogisticUnit) {
s_log.Error("CHECK DATA IN LOG - ItemCode: " + LIGR.ItemCode);
s_log.Error("CHECK DATA IN LOG - Quantity: " +
LIGR.Quantity.ToString());
foreach (PackagingTypeInfo P in LIGR.FullListOfPackagingTypes){
s_log.Error("CHECK DATA IN LOG - Uom: " + P.PackagingTypeName);
s_log.Error("CHECK DATA IN LOG - Quantity: " + P.Quantity.ToString());
}
}
}
}
```

From:
https://wiki.produmex.name/ - **Produmex**

Permanent link:
https://wiki.produmex.name/doku.php?id=implementation:wms:wms_scripting_site:example_solutions

Last update: **2024/11/18 09:47**