

DEVICE LIST

This section lists examples of devices on which Produmex WMS has been tested and successfully deployed.

1. MICROSOFT WINDOWS OPERATING SYSTEM

Datalogic Falcon X4 (WEC7) OS: Microsoft Windows Embedded Compact 7 WLAN: TI 802.11 a/b/g/n SCREEN: 3.5" TFT QVGA (240*320 pixels) MEMORY: 1 GB RAM / 8 GB Flash memory CPU: TI OMAP4 @ 1 GHz BATTERY: 3.7V 5200mAh KEYBOARD OPTIONS: 29-key numeric, 29-key functional numeric or 52-key alphanumeric EXTRA INFO: Upgradable to Android 4.4	
Datalogic Skorpio X4 (WEC7) OS: Microsoft Windows Embedded Compact 7 WLAN: TI 802.11 a/b/g/n SCREEN: 3.5" TFT QVGA (240*320 pixels) MEMORY: 1 GB RAM / 8 GB Flash memory CPU: TI OMAP4 @ 1 GHz BATTERY: 3.7V 3000mAh (std) or 3.7V 5200mAh (ext) KEYBOARD OPTIONS: 50-key full alphanumeric, 38-key functional or 28-key numeric keyboard EXTRA INFO: Upgradable to Android 4.4	
Honeywell Dolphin 60 Windows Embedded Handheld 6.5 Classic WLAN IEEE 802.11 b/g/n 2.8" QVGA 240x320 pixels Memory: 256MB RAM CPU:800MHz	

Honeywell CN75

OS: Microsoft Windows Embedded Handheld 6.5
WLAN: 802.11 a/b/g/n
SCREEN: 3.5" TFT VGA (480*640 pixels)
MEMORY: 2GB RAM /16 GB Flash memory
CPU: TI 1.5 GHz OMAP 4470 dual-core
BATTERY: 3.7V 4000 mAh
KEYBOARD OPTIONS: 57-key qwerty or 29-key numeric



M3 OX-10 (WM)-WSB-BGN-1D-AN1

Windows Embedded Handheld 6.5
WLAN IEEE 802.11 b/g/n
3.5" QVGA (WinCE) 240x320 pixels
Battery Li-Ion 3300mAh3.5"
Memory:256MB/1GB
CPU:833MHz



Honeywell CK65-L0N-E8C214E

CK65, 4GB/32GB Memory, Large Numeric, 6803 Gen8, Camera, SCP, GMS, Standard Environment, Enhanced Durability, WW Mode



2. GOOGLE ANDROID OPERATING SYSTEM

Zebra MC3300 OS: Android 8.1 (Oreo) WLAN: 802.11 a/b/g/n/ac/d/h/i/k/r/v/w SCREEN: 4" TFT WVGA (768*480 pixels) MEMORY: 2GB/16GB (std), 4GB/16GB (Premium), 4GB/16GB (Premium+) CPU: Qualcomm® APQ8056, 1.8GHz Hex-Core, 64-bit BATTERY: 2740mAh (std), 5200mAh (High capacity) KEYBOARD OPTIONS: Numeric (29 Key), Function Numeric (38 Key), Alpha Numeric (47 Key)	
Zebra MC9300 OS: Android 8.1 (Oreo) WLAN: 802.11 a/b/g/n/ac/d/h/i/k/r/v/w SCREEN: 4"3 TFT WVGA (768*480 pixels) MEMORY: 4GB RAM/32 GB Flash CPU: Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz BATTERY: 3.6V 7000mAh, 3.6V 5000mAh (Freezer) KEYBOARD OPTIONS: 58 Key Alpha-Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/Calculation	
Honeywell CN75 OS: Android 6.0 Marshmallow WLAN: 802.11 a/b/g/n SCREEN: 3.5" TFT VGA (480*640 pixels) MEMORY: 2GB RAM /16 GB Flash memory CPU: TI 1.5 GHz OMAP 4470 dual-core BATTERY: 3.7V 4000 mAh KEYBOARD OPTIONS: 57-key qwerty or 29-key numeric	

Honeywell CN80

OS: Android 8
WLAN: IEEE 802.11 a/b/g/n;
W-iFi certified 2x2 MIMO
support
SCREEN: 4.2" LCD FWVGA (480*854 pixels)
MEMORY: 3GB / 4GB RAM / 31GB Flash
memoryCPU: 2.2 GHz Qualcomm
Snapdragon 660 octa-core BATTERY:
3.85V 5800 mAh
KEYBOARD OPTIONS: 40-key qwerty or 23-key
numeric



ZEBRA MC9200

Android 4.4.4 KitKat
WLAN 802.11 a/b/g/n
3.7" Colour VGA 640x480 pixels
Memory: 1GB RAM
1D/2D Scanner



HONEYWELL DOLPHIN 75E

Android 6.0 Marshmallow with GMS
WLAN 802.11 a/b/g/n/ac
4.3" WVGA 480x800 pixels
Memory: 2GB RAM
1D/2D Scanner



HONEYWELL CT40-L0N-2SC110E

4GB/32GB, 5' HD, N6603 Standard Range Imager, 13MP, 802.11 a/b/g/n/ac/r/k/mc, WLAN, BT5.0, Android7.0, 4090mAh, WW mode



Honeywell Dolphin CT60



- OS: Android version guaranteed from 7.1 to at least 11/R
- WLAN: IEEE 802.11 a/b/g/n/ac 802.11r
- VPN: IPSec V4/L2TP, PPTP
- Memory: 3 GB/4 GB DDR4 RAM, 32 GB Flash
- Display: 118 mm (4.7 in) High Definition (1280 x 720) bright color LCD
- Touch Panel: multi-touch, capacitive
- Keypad: On-screen customizable keypad, dual-action side scan triggers, volume up/down, camera, power button
- Decode Capabilities: Honeywell N6603SR, N6703SR, or N6703HD Slim Imager Engines (1D/2D barcode symbologies)
- Camera: 13-megapixel color camera, 4K video with image stabilization
- Push to Talk (PTT): Supported
- Bluetooth: V5.0 Bluetooth and BLE Supported
- Audio: Speaker, dual microphone support with noise cancellation. PTT support and Bluetooth® wireless headset support
- NFC: Integrated Near Field Communication
- GPS Supported Protocols: Simultaneous GNSS Receiver Support for A-GPS, GLONASS, Qualcomm Gen9 position engine, Galileo, and BeiDou
- Cellular Radio: LTE Advanced Support, Supports VoLTE, GSM/GPRS/EDGE Quad-Band (850/900/1800/1900 MHz)
- Sensors: Ambient light sensor, proximity sensor, accelerometer, gyroscope, magnetometer, pressure sensor
- Dimensions: 160 mm x 82.5 mm x 19 mm (6.3 in x 3.2 in x 0.75 in)
- Weight: 350 grams (12.4 oz) with battery pack
- Battery: Li-Ion, 3.6 V, 4040 mAh with integrated battery diagnostics
- Hours of Operation: 12+ hours

EDA61K-1

Android 9 GMS
Numeric Keypad, WLAN, 3G/32G,
EX20 scan engine, 4 inch WVGA



EDA61K-1NUB34PGOK

Android 9 GMS
Numeric Keypad, WWAN, 3G/32G,
EX20 scan engine, 4 inch WVGA



Honeywell CK65L0N

- Android 8.0 Oreo
- 51-key alpha or 38- or 30-key numeric keypad
- WLAN: IEEE 802.11 a/b/g/n/ac
- VPN: IPSec V4/L2TP, PPTP
- Memory: 2 GB/4 GB DDR4 RAM, 32 GB Flash
- Display: 10.16 cm (4 in) 480 x 800 bright color LCD with backlight,
- Camera: 13.0-megapixel color camera
- Battery: Li-Ion, 7,000 mAh Smart Battery



Honeywell Dolphin CT40-L0N-1NC110E

2GB/ 32GB, 5" HD, N3601 Standard Range Imager, 13MP, 802.11a/b/g/n/ac, WLAN, Bluetooth 5.0, Android 7.0, 4090 mAh, WW mode



Honeywell CT60-L1N-ASC210F

Android 7.1.1, WWAN, 802.11a/b/g/N/AC/R/K/MC, Bluetooth 5.0, 2D Imager (N6603), 3GB/32GB Memory, 13MP Camera, Battery 4,040 mAh



Honeywell CT60-L1N-BFP210E

Android (9.0), Cam (13MP), 11,9cm (4,7"), Bluetooth, Wi-Fi (802.11ac), 4G (LTE), NFC, 1280x720 pixels, Qualcomm Octa Core, 2.2GHz, RAM: 4 GB, Flash: 32 GB, , IP68, incl.: battery, 4000mAh



3. TOUCHSCREENS

D4POS MRP-120 Vision Series	
MRP-127 17" TFT LCD with ELO touch (USB) Slim housing and metal housing Brightness (cd/m2): 300 Resolution: 1280 x 1024 Dimensions: 378 x 180 x 367 mm	
MRP-129 19" TFT LCD with ELO touch (USB) Slim housing and metal housing Brightness (cd/m2): 300 Resolution: 1280 x 1024 Dimensions: 422 x 180 x 401 mm	
4POS MRP-255 Booster Series	
MRP-255 Booster black 15" TFT LCD with ELO touch (USB) Aluminum stand Brightness (cd/m2): 350 Resolution: 1024 x 768 Dimensions: 377 x 231 x 344 mm	

3M™ MicroTouch™ Display M1700SS (17")

17" TFT LCD with 3M touch (USB/serial)
 Brightness (cd/m2): 270
 Resolution: 1280 x 1024
 Dimensions: 405 x 413.3 x 247 mm


3M™ MicroTouch™ Display M1500SS (15")

15" TFT LCD with 3M touch (USB/serial)
 Brightness (cd/m2): 225
 Resolution: 1024 x 768
 Dimensions: 408 x 398.3 x 258.7 mm


Microtouch OF-150P-A1 (15")

15" TFT LCD with touch (USB-HID Type B)
 Brightness (cd/m2): 350 (no touch), 300 (P-CAP)
 Resolution: 1024 x 768
 Dimensions: 356.9 x 280.9 x 52.3 mm


Microtouch OF-170P-A1 (17")

15" TFT LCD with touch (USB-HID Type B)
 Brightness (cd/m2): 250 (no touch), 2015 (P-CAP)
 Resolution: 1280 x 1024
 Dimensions: 394.0 x 330.0 x 57.1 mm



Microtouch OF-190P-A1 (19")

15" TFT LCD with touch (USB-HID Type B)
Brightness (cd/m2): 250 (no touch), 215 (P-CAP)
Resolution: 1280 x 1024
Dimensions: 432.9 x 360.3 x 58.4 mm



4. LABEL PRINTERS

Usually there is no compatibility problem when using a label printer which is connected to or reachable from the server machine with Crystal Reports with a windows driver.

Zebra printers with ZPL II language are also supported as a network printer, a connected local printer on the server or a reachable shared printer.

Intermec PB32 Rugged Mobile Label Printer (WiFi)

Mobile printer, can be attached to belt
203 dpi, thermal
WiFi - Network printer
Works with WH9 / Crystal Reports



Zebra S4M Direct Thermal Printer (USB, Ethernet or WiFi)

MResolution: 203 dpi
Print Width: 4: inch
Reports: ZPL or Crystal Reports
Flash Memory: 4 MB
Connectivity: USB, 10/100 Network adapter or
WiFi is an extra option



Zebra ZT231

MResolution: 203 dpi
Print Width: 4.09 inch
Reports: ZPL
Flash Memory: 256 MB / 256
MB SDRAM
Connectivity: USB, 10/100 Ethernet or
802.11ac Wi-Fi



Zebra ZT111

MResolution: 203/30
 dpi
 Print Width: 4.09 inch
 Reports: ZPL
 Flash Memory: 256 MB / 256
 MB SDRAM
 Connectivity: USB, 10/100 Ethernet or
 802.11ac Wi-Fi



Zebra ZT400 Series

MResolution: 203 /
 300 / 600 dpi
 Print Width: 4.09 /
 6.6: inch
 Reports: ZPL
 Flash Memory: 512 MB / 256
 MB SDRAM
 Connectivity: USB, 10/100 Ethernet or
 802.11ac Wi-Fi, Parallel



Zebra ZQ600 Plus Series

MResolution: 203 dpi
 Print Width: 1.9 / 2.8
 / 4.1 inch
 Reports: ZPL or Crystal Reports
 Flash Memory: 512 MB / 256
 Mb SDRAM
 Connectivity: USB 2.0, 10/100 Ethernet or
 802.11ac Wi-Fi



pHoneywell PB Series

MResolution: 203 dpi
 Print Width: 2.25 /
 3.3 / 4.39 inch
 Reports: ZPL or Crystal Reports
 Flash Memory: 64 MB / 16 MB
 SDRAM
 Connectivity: USB 2.0, RS-232 Serial,
 Bluetooth v2.0 802.11b/g

